

Electric Hoist



PA400B



Features

UL/CUL approval
Upper limit device
Thermal protection terminal
Protection class IP40



Method of use	Single hook	Double hook
Rated Volt(V)	120	
Input Power(W)	850	
Rated lifting weight(kg)	200	400
Lifting speed(m/min)	10	5
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52 × 41 × 17	
G.W./N.W.(kg)	35/33	

PA500B



Features

UL/CUL approval
Upper limit device
Thermal protection terminal
Protection class IP40



Method of use	Single hook	Double hook
Rated Volt(V)	120	
Input Power(W)	1000	
Rated lifting weight(kg)	250	500
Lifting speed(m/min)	10	5
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52 × 41 × 17	
G.W./N.W.(kg)	36/34	

PA600B



Features

UL/CUL approval
Upper limit device
Thermal protection terminal
Protection class IP40



Method of use	Single hook	Double hook
Rated Volt(V)	120	
Input Power(W)	1250	
Rated lifting weight(kg)	300	600
Lifting speed(m/min)	10	5
Lifting height(m)	12	6
Qty/CTN(PCS)	2	
Packing dimension(cm)	52 × 41 × 17	
G.W./N.W.(kg)	37/35	